




肖特基二极管
反向电压 100 V
正向电流 20 A

Schottky Barrier Rectifiers
Reverse Voltage 100 V
Forward Current 20 A



特征 Features

- 反向漏电流低 Low reverse leakage
- 正向压降低 Low forward voltage
- 正向浪涌承受能力强 High forward surge capability
- 沟槽工艺 Trench schottky technology
- 高信赖性 High reliability
- 引线和管体皆符合RoHS标准 Lead and body according with RoHS standard
- 型号后缀“-F”标记无卤素产品 Green compound with suffix "-F" on Marking

机械数据 Mechanical Data

- 封装外形: ITO-220AB 塑封 Case: ITO-220AB Molded plastic
- 环氧树脂 : UL易燃等级 : 94V-0
Epoxy: UL 94V-0 rate flame retardant
- 引脚 : 镀锡,无铅 Lead: Pure tin plated, lead free
- 安装位置: 任意 Mounting Position: Any
- 安装扭距: 推荐值 0.3牛*米 Mounting torque : Recommend 0.3 N*m

极限值和温度特性 TA = 25°C 除非另有规定。
Maximum Ratings & Thermal Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

参数 Parameter	符号 Symbols	TBRF20100CTI	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	100	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	70	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	100	V
最大正向平均整流电流 Maximum average forward rectified current	I _{F(AV)}	20	A
正向不重复浪涌电流 8.3 ms单一正弦半波 Non-repetitive peak forward surge current 8.3 ms singlehalf sine-wave	I _{FSM}	150	A
典型热阻 Typical thermal resistance (Note 1)	R _{θJC}	4	°C/W
最高工作结温 maximum operating junction temperature	T _J	150	°C
存储温度 Storage temperature range	T _{STG}	-55 --- +150	°C

备注 Note:

- 1) 安装在PCB板上 , 从PN结到管体的热阻。
- 1) Thermal resistance from junction to case , PCB mounted.

电特性 TA = 25°C 除非另有规定。

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

参数 Parameter	符号 Symbols	TBRF20100CTI	单位 Unit
典型正向电压 @IF=2.0A Typical forward voltage	V _F	0.50	V
最大正向电压 @IF=10.0A Maximum forward voltage	V _F	0.75	V
最大反向电流 @V _{DC} Maximum reverse current	I _R	100	uA



特性曲线 Characteristic Curves

